

12PPM fully featured professional printer

- Professional print quality at 1200dpi class
- Exceptional 12 page per minute printing
- Brothers Printing System for Windows, PCL6, IBM & EPSON emulations
- Printer driver for iMac G3 & G4 supplied
- Optional second tray increases capacity to 500 sheets
- Parallel and USB ports for easy connection
- Easily adaptable for use on a network
- Useful 'On-screen Interactive Help' and 'Quick Print Set-up' for Windows
- Long life consumables



HL-1250

LASER PRINTER

To cope with a high day-to-day demand in a professional environment, a printer must provide excellent print quality, speed, reliability, versatility and economy. The Brother HL-1250 performs equally well in each of these areas.

Impressive print quality, at up to 1200dpi class gives crisp type and clear graphics. A powerful processor, large 4Mb memory and optimised software maximise print speed, so you can print exceptionally fast, at up to 12 pages per minute.

The HL-1250 has multiple emulations and printer drivers ensuring compatibility with a wide range of computing environments. Parallel and USB ports as standard allow for easy connection.

An optional 250 sheet second paper tray (LT-400) increases input capacity to 500 sheets for high

volume printing. Optional Ethernet interfaces support enables connection to a network.

The Windows drivers also include useful features such as 'on-screen Interactive Help' function and a 'Quick Print Setup' function, enabling you to control printer settings direct from your task bar.

Power, toner and paper saving

facilities make significant cost savings, and it's this combination of economical performance and superior build quality, ensuring a long life, that makes the HL-1250 an ideal print solution for all applications.







Specifications

engine

Technology Print speed Warm up time First print time Resolution

controller

Processor Memory

(optional) Interface (standard) (optional)

(standard)

Emulation

Auto emulation switching Resident fonts

Printer driver

network

Optional Solution

Interface

Protocol

control panel

Display On/Off Switch

paper

Paper tray input (standard) (optional) (output) sheet sizes sheet weight

electrophotographic up to 12ppm less than 45 sec less than 15 sec up to 1200x600dpi up to 600x600dpi with DOS and iMac/G3/G4

MB86832 66MHz

1 SIMM slot-up to max of 36Mb IEEE 1284 bi-di Parallel, USB 10Base T or 10Base2 PCL6/Epson FX-850/ IBM Proprinter XL

49 scaleable fonts, 12 bitmap fonts

Windows 3.1/95/98/NT 4.0 Mac OS 8.5/OS 8.6

NC-2010P (external) NC-2010X (internal) 10Base T (NC-2010P) 10Base2 or 10Base T (NC-2010X) TCP/IP, IPX/SPX, DEC LAT, NetBEUL DLC/LLC Banyan Vines (NC-2010P only)

41FDs Yes

250 sheets 250 sheet lower tray LT-400 150 sheets face down A4. B5. A5. A6 64-105g/m2

Manual feed input

> sheet weight other media

Multiple page printing

Duplex

supplies/life

Toner

Drum

additional features

Features

Other software

other

Dimensions (mm) Weight

consumption (printing) (standby)

(sleep) Noise level (printing) (standby)

Ecology (toner save) (power save)

product reference

HL-1250 4Mb HL-1250 8Mb HL-1250LT 4Mb HL-1250LT 8Mb 1 sheet min 70(w)x116(d)mm max 216(w)x356(d)mm

64-158g/m2 OHP, envelopes, labels 2 in 1, 4 in 1, 9 in 1, 16 in 1 25 in 1, 1 in 2x2, 1 in 3x3 1 in 4x4, 1 in 5x5 Manual

TN-6300: 3,000 A4 pages@5% TN-6600: 6,000 A4 pages@5% DR-6000: 20,000 A4 pages (1 page per job)

On-screen Interactive Help. Quick Print Set-up, Watermark, Status Monitor function, Automatic e-mail printing RPC (Remote Printer Control in DOS)

360(w)x370(d)x235(h) 20.3lb/9.2kg inc. toner/drum

Average 340W Max 80W Max 6W 49dBA 27dBA Yes

10487 10880 10881

10882





other media

















