

12PPM network printer, ideal for small work groups

- Built-in Ethernet 10/100Base TX support
- Professional print quality at 1200dpi class
- Exceptional 12 page per minute printing

Brothers Printing System for Windows, PCL6, IBM, EPSON. Postscript level 2 compatible emulations

- Printer driver for iMac, G3 & G4 supplied
- Optional 2nd tray increases capacity to 500 sheets
- Parallel and USB ports for easy connection

Useful 'On-screen Interactive Help' and 'Quick Print Set-up' for Windows

Long life consumables

brother

HL-1270N LASER PRINTER

In answer to today's increasing need for network printing, the HL-1270N has built-in network capabilities, supporting Ethernet 10/100Base TX, with all major protocols; TCP/IP, IPX/SPX* and EtherTalk*.

Networked HL-1270Ns can be managed remotely, using Brother's own BRAdmin 32-bit application, allowing your IT administrator to see and change printer and network settings. You can also connect to the printer's built-in Web server, using your favourite Web browser. For additional compatibility, HP's JetAdmin and Web JetAdmin are also supported. Both print speed and quality are exceptional, as the HL-1270N prints up to 12 pages per minute, at 1200dpi class. The standard input capacity of 250 sheets can be increased to 500 with an optional 250 sheet second paper tray (LT-400). For added flexibility, the Brother Card Monitor software is designed to handle electronic forms and logos stored in the Flash memory with ease.

Incorporating power, toner and paper saving facilities, the HL-1270N laser printer is economical to run, and makes a cost-effective solution for any networking environment.

Specifications

engine

Technology Print speed Warm up time First print time Resolution

Controller Processor Memory (standard) (optional) Interface (standard) coptional) Emulation Auto emulation switching Resident fonts Printer driver (standard)

network

Solution Interface Protocol

Management

control panel

Display On/Off Switch paper handling Paper tray input (standard) (optional) output electrophotographic up to 12ppm less than 45 sec less than 15 sec up to 1200x600dpi with Windows up to 600x600dpi with DOS and iMac/G3/G4

MB86832 66MHz 4Mb 1 SIMM slot-up to max of 36Mb IEEE 1284 bi-di Parallel, USB 10/100Base TX (auto detection) None PCL 6/Epson FX-850/ IBM Proprinter XL/Postscript 2 language emulation Yes 66 scaleable fonts, 12 bitmap fonts

Windows 3.1/95/98/NT4.0 Mac OS 8.5/OS 8.6

BR-Net (Standard) 10/100Base TX TCP/IP, SNMP, MIB II, BOOTP, DCHP, WINS, LPR/LPD, PORT 9100, POP3/SMTP, SMB (NetBIOS over IP), IPX/SPX, AppleTalk (Dec 99) BRAdmin 32-bit, Web browser (HTTP), JetAdmin/Web JetAdmin compatible

4 LEDs Yes

250 sheets 250 sheet lower tray LT-400 150 sheets face down

(input)	

sheet weight other media Multiple page printing

sheet sizes

sheet weight

other media

sheet sizes

1 sheet

Duplex

supplies/life

Drum

additional features Features

Other software

C

oth	er	
	Dimensions (mr Weight Power	(ת
	consumption	(printing) (standby) (sleep)
	Noise level	(printing) (standby)
	Ecology	(toner sav (power sa

product reference

HL-1270N 4Mb
HL-1270N 8Mb
HL-1270NLT 4Mb
HL-1270NLT 8Mb

A4, B5, A5, A6 64-105g/m2 OHPManual feed

1-1270

WEB

nelP

Interactive

min 70(w)x116(d)mm max 216(w)x356(d)mm 64-158g/m2 OHP, envelopes, labels 2 in 1, 4 in 1, 9 in 1, 16 in 1 25 in 1, 1 in 2x2, 1 in 3x3 1 in 4x4, 1 in 5x5 Manual

TN-6300: 3,000 A4 pages@5% TN-6600: 6,000 A4 pages@5% DR-6000: 20,000 A4 pages (1 page per job)

Flash memory (512kb), On-screen Interactive Help, Quick Print Set-up, Watermark Automatic e-mail printing RPC (Remote Printer Control in DOS)

360(w)x370(d)x235(h) 20.3lb/9.2kg inc. toner/drum

Average 340W Max 80W Max 12W 49dBA 27dBA Yes Yes

10489	
10883	
10884	
10885	

e)

ve)





Mac



Specifications subject to change without notice. Brother is a registered trademark of Brother Industries Ltd Apple, the Apple logo and the Mac logo are trademarks of Apple Computer, Inc., registered in the United States and other countries.