



HL-5050

Need a mono printer that can give your business a little bit more? You should opt for the HL-5050.

The HL-5050 is the ideal printing solution for your busy, modern office. It has a print speed of up to 16 pages per minute, up to 2400 x 600 dpi resolution and a "High Speed" USB 2.0 port that comes as standard. Couple this with an additional 250 sheet* paper cassette** and a 50 sheet* multi-purpose tray, the HL-5050 is the truly versatile printer that your office demands.

The HL-5050 has been optimised to make it compatible with a wide range of computing environments, and also includes 16MB of standard memory, expandable up to 144MB, with optional network connectivity.

Brother have also made the HL-5050 as quick and easy to install, so you'll be up and running in minutes.

Plus, for additional peace of mind, you can enjoy direct access to the Brother corporate www.brother.com.au web site as well as the solutions website solutions brother.com

bode

KEY FEATURES:

- Up to 16 pages per minute print speed
- HQ 1200 resolution
- 16MB standard memory, expandable to up to 144MB
- Aligh Speed USB 2.0 and Parallel ports as standard
- Optional external network 10/100 Base-TX Ethernet connectivity (NC-2100P) supports TCP/IP, NetBEUI and Appletalk

- Optimised drivers for Windows* 95/98/Me/NT* 4.0/2000/XP. Mac* OS 8.6-9.2, OS X 10.1 - 10.2, DOS compatible Linux compatible
- PCL*6, BR-Script* 3 (Postscript* Level 3 Language Emulation), IBM* Proprinter XL Epson*FX-850 emulations
- Up to 250 sheet* paper cassette, Up to 50 sheet* multi-purpose tray
- Optional up to 250 sheet* lower tray (LT-5000)
- Easy replacement, long life supplies

Technical Specifications

GENERAL

Print Speed First Print Tim Resolution Up to 16ppm (A4) Less than 12 seconds 2,400 x 600dpi (Win/Mac) 600 x 600dpi (Win/Mac/DOS) 300 x 300dpi (Win/Mac/DOS)

16MB, expandable up to 144MB

Mac* OS 8.6-9.2, OSX 10.1/10.2

GDI Driver Interactive Help

Up to 250 Sheets*

Manual Duplex

Yes Yes

USB 2.0, IEEE 1284 Parallel 10/100BaseTX Ethernet (to order quote: NC-2100P)

PCL*: 66 Scalable Fonts, 12 Bitmap Fonts

Up to 50 Sheet* Multi-purpose Tray
Up to 50 Sheets* (to order quote: LT-5000)
Up to 150 Sheets* Face Down

TCP/IP, NelBEUI, Appletalk (to order quote: NC-2100P)
PCL*6, BR-Script3 (PostScript* Level 3 Language Emulation),
IBM Proprinter XL, Epson FX-850

PCL* / BR-Script 3 Driver for Windows* 95/98/Me/NT*4.0/

133MHz

CONTROLLER

Processor Memory Interface Optional Interface Network Protocols (o

Optional Interface
Network Protocols (optional)***
Emulation

Resident Fonts Barcodes

SOFTWARE

Macintosh®

Macintosh Linux Utilities

CONTROL PANEL

3 Colour Status LED Go and Job Cancel button

PAPER HANDLING

Input Paper Capacity

Optional Input Paper Capacity
Output Paper Capacity

Duplex

MEDIA SPECIFICATIONS

Media Types (Paper Tray) (Manual Feed Slot)

Media Weights (Paper Tray) (Manual Feed Slot) Media Sizes (Paper Tray) (Manual Feed Slot) Plain Paper, Bond Paper, Recycled Paper and Transparencies Plain Paper, Bond Paper, Recycled Paper, Transparencies, Labels and Envelopes

60 – 161gsm 60 – 105gsm

A4, Letter, B5(ISO), A5, B6 (ISO), A6, Executive and Legal Custom: 69.8mm to 220mm x 116mm to 406.4mm

SUPPLIES****

Toner (Standard Yield) (High Yield) Drum



TN-7300, up to 3,300 A4/Letter Pages @ 5% coverage TN-7600, up to 6,500 A4/Letter Pages @ 5% coverage DR-7000, up to 20,000 A4/Letter Pages The frequency of replacement of consumables will vary depending on the complexity of the prints, the percentage of coverage, paper

on the complexity of the prints, the percentage of coverage, paper size, page per job and the type of media. For example, transparencies, glossy coated paper will result in a shortened life of such supplies

ACCESSORIES

LT-5000 NC-2100P

DIMENSION / WEIGHT

Dimension Weight Up to 250 Sheet* Lower Tray 10/100 Base-TX Ethernet Network Interface

(382mm width) x (401mm depth) x (252mm height) 11.5kg

OTHERS

Power Consumption Noise Level Power Save Mode Toner Save Mode Printing / Standby / Sleep 460/75/5W or less Printing / Standby 50/30db or less

Yes Yes

Contact:



Brother International Australia Pty Ltd

Corporate website: www.brother.com.au

Printer solutions website: solutions.brother.com

NSWIACT 7 Khartoum Rd. North Ryde NSW 2113 Phone: (02) 987 4344 Fax: (02) 9870 7234 VIC 43 Carrington Rd. Box Hill VIC 3128 Phone: (03) 9899 4844 Fax: (03) 9899 4833 QLD/NT Unit 4, 57 Miller St. Murrarie OLD 4172 Phone: (07) 3348 9266 Fax: (07) 3348 9366 SA/TAS Unit 4, 13 King William Rd. Unley SA 5061 Phone: (08) 8272 1300 Fax: (08) 8272 1199 WA 117 Great Eastern Highway Belmont WA 6104 Phone: (08) 9478 1955 Fax: (08) 9277 2177