

LASER PRINTER
 DIGITAL COPIER
 COLOR SCANNER
 PC FAX



At your side.

OCHOR

BROTHER INTERNATIONAL CORPORATION



### MFC-9700

## **ATURES**

Page Auto Document Feeder er Quick Scan – up to 2 seconds page3

4K bps High-Speed Fax Modem Station Auto Dialing

B Total Memory (up to 600 pages\*)

adcasting (up to 158 locations) al Access lets you scan a fax into mory while another is being received nultaneous Operations let you perform

## SER PRINTER

functions at once

to 15 Pages per Minute Printing e 600 x 600 dpi Laser Output allel and USB Interfaces Standard rallel cable included)

Sheet Paper Cassette Capacity tional 2nd 250 Sheet Cassette available<sup>t</sup>) rks with Windows®, DOS, (PCL4) and c™/iBook™/G3/G4 applications minimum system requirements below)





Computer Place
Operating Syst

Vindows®

perating

Systems

## DIGITAL COPIER

- Versatile Flatbed Design for copying from bound documents
- Up to 15 cpm Copy Speed
- 600 dpi Copy Output
- No PC required
- Multi-Copying, up to 99, with Sorting
- Reduce or Enlarge from 25% to 400% in one percent increments

# COLOR SCANNER FEATURES

- Flatbed Design for scanning from bound documents
- Color or Black & White Scanning
- Up to 9600 x 9600 dpi (Interpolated) Resolution and up to 600 x 2400 dpi (Optical) Resolution
- Easy to use Desktop interface with "Drag and Drop" Filing and Linking
- Includes award-winning ScanSoft™ PaperPort® and TextBridge® OCR software

# **FEATURES**

- Includes Brother PC Fax Software for sending or receiving faxes via your PC
- Broadcast faxes from your PC
- Works with Windows® and iMac™/iBook™/G3/G4

#### MFC-9700 Optional Supplies & Accessories

brother

Standard Toner Cartridge 3,000 pages per cartridge▼ High Yield Toner Cartridge 6,000 pages per cartridge▼ TN-430: Drum Unit

DR-400: LT-400:

Second Paper Cassette (Holds an additional 250 Pages) Network (LAN) Board

Requires additional purchase Based on 5% page coverage Based on Brother #1 Chart with MMR coding and standard resolution

Minimum System Requirements

Platform /stem Version	Processor Minimum Speed	Minimum RAM	Recommended RAM	Available Hard Disk Space	CD-ROM Drive Minimum Speed
95, 98, 98SE	Pentium 75MHz	24MB	32MB	50MB	2X
Me	Pentium 150MHz	32MB	64MB	50MB	2X
NT <sup>®</sup> Workstation 4.0	Pentium 75MHz	32MB	64MB	50MB	2X
2000 Professional	Pentium 133MHz	64MB	128MB	50MB	2X
VD	Dantium 222MU	CAMP	400MD	FOMD	27

	ХР	Pentium 233MHz	64MB	128MB	50MB	2X
Apple	OS 8.5, 8.5.1 (Printer Only)	All base models meet minimum requirements			50MB	2X
c™/iBook™/ 64 Operating	OS 8.6 — 9.1				50MB	2X
Systems	(Printer & Scanner)				50MB	2X

E: USB is not supported under Windows® 95 or Windows NT® 4.0

egistered trademarks referenced herein are the property of their respective companies.

#### BROTHER INTERNATIONAL CORPORATION

omerset Corporate Blvd., Bridgewater, NJ 08807-0911

ore information please call the Brother Fax-Back System at 1-800-521-2846 (USA),

681-9838 (Canada), or visit our web site at www.brother.com cifications are subject to change without notice. Printed in USA. CATMFC9700

#### PRODUCT SPECIFICATIONS

Approved: FCC & UL

Unit Dimensions: 19.4" x 18.0" x 16.9"

Carton Dimensions: 23.5" x 22.3" x 22.8"

Unit/Carton Weight: 33.0 lbs/46.3 lbs

UPC Code: 0 12502 60073 2

Printing Method/Speed: Electrophotography/15PPM

Compatibility: ITU Group 3

Coding Method: MH/MR/MMR/JBIG

Modulation: 14400/12000/9600/

7200/4800/2400 bps

Transmission Time: 4 seconds per page

(ITU #1 chart, JBIG)

Total Machine Memory: 8MB

Document Input Width: 5.8" to 8.5"

Recording Paper Size: 8.5" x 11"/8.5" x 14"

Paper Type for Manual Pass: Letter, Legal, A4, B5, Executive,

Envelopes, Transparencies, Laser label sheets, Custom Size

2.75" x 5" to 8.5" x 14"

Scanning & Recording Width: 8.2"

Printer Resolution: True 600 x 600 dpi

Fax Resolution: Standard: 203 x 98 lines/inch

Fine: 203 x 196 lines/inch

Superfine: 203 x 392 lines/inch

Gray Scale: 64 shades

Speaker Type: Monitor

Interfaces (standard): High-Speed Bi-Directional

Centronics Parallel (IEEE 1284 cable included) & USB interfaces

(USB cable not included)

**Emulations: Brother Printing Solution for** Windows® or iMac™/iBook™/G3/G4,

PCI 4

Utility Software: Windows® 95/98/98SE, Me,

NT® Workstation 4.0, 2000 Professional, XP, or

iMac™/iBook™/G3/G4, OS 8.5-9/14

Power Supply: 120V, 50/60Hz

Power Consumption: Operating (Copying): 850W or less Standby: 60W or less Sleep Mode: 9W or less

Noise Level: 53 dbA (printing)

30 dbA (standby)

Operating Environment: 50° to 90.5° (F)

OS 8.5, 8.5.1 support printing only

