

# LASER MFC

FLATBED

MULTI-FUNCTION CENTER®

FAX • LASER PRINTER • DIGITAL COPIER • COLOR SCANNER • PC FAX

## MFC-9800



UPTO  
**FAST 15**  
PPM  
PRINTING  
& COPYING

**SUPER G3**  
33.6K bps High-Speed FAX

WORKS WITH  
WINDOWS® iMac™/G3  
iBook™/G4

At your side.™

# brother®

©2001 BROTHER INTERNATIONAL CORPORATION

# LASER MFC

FLATBED MULTI-FUNCTION CENTER

## MFC-9800



### FAX FEATURES

- 50 Page Auto Document Feeder
- Super Quick Scan – up to 2 seconds per page\*
- 33.6K bps High-Speed Fax Modem
- 132 Station Auto Dialing
- 8MB Total Memory (up to 600 pages\*)
- Broadcasting (up to 182 locations)
- Dual Access lets you scan a fax into memory while another is being received
- Simultaneous Operations let you perform two functions at once

### LASER PRINTER FEATURES

- Up to 15 pages per minute Printing
- True 600 x 600 dpi Laser Output
- Parallel and USB Interfaces Standard (Parallel Cable Included)
- 250 Sheet Paper Cassette Capacity (Optional 2nd 250 Sheet Cassette available†)
- Works with Windows®, DOS, (PCL5e) and iMac™/iBook™/G3/G4 applications (see minimum system requirements below)



### DIGITAL COPIER FEATURES

- Versatile Flatbed Design for copying from bound documents
- Up to 15 cpm Copy Speed
- 600 dpi Copy Output
- No PC required
- Multi-Copying, up to 99, with Sorting
- Reduce or enlarge from 25% to 400% in one percent increments

### COLOR SCANNER FEATURES

- Flatbed Design for scanning from bound documents
- Color or Black & White Scanning
- Up to 9600 x 9600 dpi (Interpolated) Resolution and up to 600 x 2400 dpi (Optical) Resolution
- Easy to use Desktop interface with "Drag and Drop" Filing and Linking
- Includes award-winning ScanSoft™ PaperPort® and TextBridge® OCR software

### PC FAX FEATURES

- Includes Brother PC Fax software for sending or receiving faxes from your PC
- Broadcast faxes via your PC
- Works with Windows® and iMac™/iBook™/G3/G4

#### MFC-9800 Optional Supplies & Accessories†

TN-430:	Standard Toner Cartridge 3,000 pages per cartridge*
TN-460:	High Yield Toner Cartridge 6,000 pages per cartridge*
DR-400:	Drum Unit
LT-400:	Second Paper Cassette (Holds an additional 250 Pages)
NC-8100h	Network (LAN) Board

use only  
GENUINE  
brother  
supplies

† Requires additional purchase  
\* Based on 5% page coverage  
\* Based on Brother #1 Chart with MMR coding and standard resolution

### Minimum System Requirements

Computer Platform & Operating System Version		Processor Minimum Speed	Minimum RAM	Recommended RAM	Available Hard Disk Space	CD-ROM Drive Minimum Speed
Windows® Operating Systems	95, 98, 98SE	Pentium 75MHz	24MB	32MB	50MB	2X
	Me	Pentium 150MHz	32MB	64MB	50MB	2X
	NT® Workstation 4.0	Pentium 75MHz	32MB	64MB	50MB	2X
	2000 Professional	Pentium 133MHz	64MB	128MB	50MB	2X
	XP	Pentium 233MHz	64MB	128MB	50MB	2X
Apple iMac™/iBook™/G3/G4 Operating Systems	OS 8.5, 8.5.1 (Printer Only)	All base models meet minimum requirements			50MB	2X
	OS 8.6 – 9.1 (Printer & Scanner)				50MB	2X
					50MB	2X

NOTE: USB is not supported under Windows® 95 or Windows NT® 4.0  
All registered trademarks referenced herein are the property of their respective companies.

### PRODUCT SPECIFICATIONS

- Approved: FCC & UL
- Unit Dimensions: 19.4" x 18.0" x 16.9"
- Carton Dimensions: 23.5" x 22.3" x 22.8"
- Unit/Carton Weight: 33.0 lbs/46.3 lbs
- UPC Code: 0 12502 60061 9
- Printing Method/Speed: Electrophotography/15PPM
- Compatibility: ITU Group 3
- Coding Method: MH/MR/MMR/JBIG
- Modulation: 33600/31200/28800/26400/24000/21600/19200/16800/14400/12000/9600/7200/4800/2400 bps
- Transmission Time: Approx. 2 seconds per page (ITU #1 chart, JBIG)
- Total Machine Memory: 8MB
- Document Input Width: 5.8" to 8.5"
- Recording Paper Size: 8.5" x 11"/8.5" x 14"
- Paper Type for Manual Pass: Letter, Legal, A4, B5, Executive, Envelopes, Transparencies, Laser label sheets, Custom Size 2.75" x 5" to 8.5" x 14"
- Scanning & Recording Width: 8.2"
- Printer Resolution: True 600 x 600 dpi
- Fax Resolution: Standard: 203 x 98 lines/inch  
Fine: 203 x 196 lines/inch  
Superfine: 203 x 392 lines/inch
- Gray Scale: 64 shades
- Speaker Type: Monitor
- Interfaces (standard): High-Speed Bi-Directional Centronics Parallel (IEEE 1284 cable included) & USB interfaces (USB cable not included)
- Emulations: Brother Printing Solution for Windows® or iMac™/iBook™/G3/G4, PCL5e
- Utility Software: Windows® 95/98/98SE, Me, NT® Workstation 4.0, 2000 Professional, XP, or iMac™/iBook™/G3/G4, OS 8.5-9/1\*
- Power Supply: 120V, 50/60Hz
- Power Consumption: Operating (Copying): 850W or less  
Standby: 60W or less  
Sleep Mode: 9W or less
- Noise Level: 53 dbA (printing)  
30 dbA (standby)
- Operating Environment: 50° to 90.5° (F)

\*OS 8.5 8.5.1 support printing only.

At your side.™  
**brother**®  
www.brother.com