USA Models	Black: P2502W
Canada & Mexico Models	Black: P2500W
Picture	ACCUTAGE A
Printing	
Technology	Electrophotographic laser monochrome
Print speed	22 ppm (A4) / 23 ppm (Letter)
First print out time	Less than 7.8s
Maximum monthly volume	15,000 pages
Recommended monthly volume	700 pages
Resolution(dpi)	Max.1,200×1,200
Printer language	GDI
Duplex Mode	Manual
Paper handling	
Paper input	150 pages
Paper output	100 pages
Media type	Plain, Thick, Transparency, Cardstock, Label, Envelope, Thin
Media size	A4, A5, A6, JIS B5, ISO B5, B6, Letter, Legal, Executive, Statement, Monarch envelope, DL envelope, C5 envelope, C6 envelope, NO.10 envelope, Japanese postcard, Folio, Oficio, Big 16k, 32k, 16k, Big 32k, ZL, Yougata4, Postcard, Younaga3, Nagagata3, Yougata2
Media weight	60~163g/m ²
General	<u> </u>
Dimensions (W \times D \times H)	337 x 220 x 178 mm (13.27 x 8.66 x 7.01 inch)
Weight (without toner cartridge)	4kg (8.82lbs)
Weight (with toner cartridge)	4.75kg (10.47lbs)
Recommended environment	Recommended temperature: 10-32°C (50°F-90°F)

	Humidity range: 20% - 80%
Power	110V Model: AC100~127V (±10%); 50Hz/60Hz; 6A 220V Model: AC220~240V (-15%,+10%), 50Hz/60Hz; 3A
Noise	Printing: 52dB Standby: 30dB
Power consumption	Printing: Average 370W Ready: 38W Sleep Mode: Less than 2 W
Operating system compatibility	Microsoft Windows Server2003/Server2008/Server2012/XP/Vista/Win7/Win8/Win8.1 (32/64 Bit) Mac OS 10.6/10.7/10.8/10.9 Linux
Connectivity	Hi-Speed USB 2.0; WiFi 802.11b/g/n
Processor speed	600MHz
Memory	128MB
Energy efficiency	ENERGY STAR® certified
Consumable *	
Toner cartridge	P*-210 Series Standard capacity (1,600 pages)
What's in the box	
	Printer x 1/ 700 page starter cartridge x 1 / USB interface cable x 1 / Power cord x 1 / CD-ROM x 1 / Quick setup guide x 1
* Average yield per toner cartridge in a	ccordance with ISO/IFC 19752 (Individual users will experience

^{*} Average yield per toner cartridge in accordance with ISO/IEC 19752 (Individual users will experience different results based on their environment and page coverage)