hp designjet





durable graphics printing

for print service providers and signmakers

hp designjet cp series printers

Print-service providers, retailers, and graphics professionals know that the HP Designjet CP Series printers are an ideal high-resolution printing solution for durable indoor and outdoor applications. While providing long-lasting, vibrant colors, and professional photoquality printing, the HP Designjet CP Series also allows RIP flexibility to easily integrate into any graphics workflow.

Whether you want to print with a preferred RIP, add a plugand-play PostScript printer to your network, or use an external high-performance Fiery RIP for file processing, there is an HP Designjet CP Series printer right for your needs. And with durable, lightfast UV inks and a wide variety of printing material, rich, vivid colors will stay true for up to five years.

All HP Designjet CP Series printers are engineered with the same technological foundation for image quality, durability, and unattended printing features.

image quality

- 600-dpi resolution
- Brilliant, accurate colors and smooth, subtle skin tones
- HP Zoomsmart scaling technology easily enlarges

any image in Microsoft Windows applications

durable printing

- Create durable, lightfast indoor and outdoor prints with pigment-based UV ink system
- Genuine HP Designjet CP Series Ink Supplies ensure long-lasting indoor prints
- Image durability warranted 24 months outdoor and five years indoor using HP Designjet CP Series UV Ink Supplies and 3M[™] Matched Component System[™]

unattended printing

- Large-capacity ink system prints up to 2000 square feet between dye-based ink system changes
- Automatic printhead alignment
- Take-up reel (optional on 36-inch models)

hp warranty and support

- One-year warranty delivers free, on-site, next-businessday service, backed by HP support centers around the world
- HP Supportpacks and service agreements allow you to extend your warranty to up to five years

hp designjet 2000cp/3000cp printers

- Requires external RIP or supplied Windows or AutoCAD drivers
- An external RIP may provide the following features:
 - Direct printing of more input file formats such as JPEG, GIF, EPS, EMP and Targa
 - Enhanced image processing algorithms, color correction and calibration features
 - Ability to handle even more media types
 - Enhanced productivity—faster information processing and printing, as well as multiperipheral support
 - Enhanced print management—job management and accounting capabilities maximize printing capacity while tracking ink and media capacity by print job
- For a list of RIP solutions available for HP Designjet printers, visit **www.hp.com/go/designjet**

- C4703A (2000cp 36 inch): \$8,995
- C4723A (3000cp 54 inch): \$13,995

hp designjet printing supplies

HP Designjet Printing Supplies maximize the performance of your HP Designjet system. The portfolio of supplies consists of high performance products for a variety of printing solutions that ensure uncompromising print quality, performance, and reliability.

The **hp** designjet printing solution—**hp** printers, ink systems and printing material—engineered and tested together to ensure uncompromising print quality, performance and reliability.

hp designjet 2500cp/3500cp printers

- Network ready—comes ready to print right out of the box
- Includes Adobe PostScript 3 RIP, 4.3 GB hard disk and HP Jetdirect network interface
- PostScript drivers for Macintosh, Windows drivers included, as well as AutoCAD drivers for Windows and DOS
- Reprint images quickly and easily from the queue
- A powerful combination of color management tools eliminates guesswork. Colors are consistent and accurate from screen to print:
 - Pantone certified colors
 - Standard press emulations support for SWOP, EuroScale, and TOYO
 - ICC profiles for Windows and Macintosh
 - Apple ColorSync compatibility
 - Automatic color calibration
 - Can also be connected to external RIPs
- C4704A (2500cp 36 inch): \$11,995
- C4724A (3500cp 54 inch): \$16,995

hp designjet 2800cp/3800cp printers

- Network ready—comes ready to print right out of the box
- Supplied Fiery X2-CP RIP provides powerful performance via customized HP Varware print modes and wide-mask technology, Fiery RIPChips, customer ASICs, and a MIPS R5000 motherboard with a 200 MHz CPU
- Increased productivity with Fiery WebTools, Fiery Spooler, and Fiery Downloader remote printer management utilities
- Fiery NetWise[™] networking architecture offers seamless connectivity to any workgroup
- Special built-in media simulations fine-tune final output
- Pantone color matching
- Standard press emulations support for SWOP, Euroscale, and DIC
- Apple ColorSync compatibility
- C6085A (2800cp 36 inch): \$11,995
- C6084A (3800cp 54 inch): \$18,995

hp designjet cp series ink supplies

dye	UV	color	ink volume	
C1806A	C1892A	black	410 ml	
C1807A	C1893A	cyan	410 ml	
C1808A	C1894A	magenta	410 ml	
C1809A	C1895A	yellow	410 ml	

hp printing material

HP Printing Material offers a broad range of solutions, from premium products for uncompromising image quality to economical products for best value and flexibility.

HP Printing Material for Dye Applications: HP Coated Paper, HP Heavyweight Coated Paper, HP Paper Based Semi-Gloss, HP Studio Canvas, HP Colorfast Adhesive Vinyl, HP High-Gloss Photo Paper, HP Semi-Gloss Photo Paper.

HP Printing Material for UV Applications: HP Heavyweight Coated Paper, HP Studio Canvas, HP Colorfast Adhesive Vinyl, HP Banners with Tyvek $^{(\!R)}$, HP Colorlucent Backlit UV.

For complete HP Printing Material product information, compatibility and printing tips, visit **www.hp.com/go/designjet** and select "Printing Material."

hp designjet cp series printers

orint technology	HP Color Thermal Inkjet					
print technology		Normal / made - the state	Rost/photo			
print performance* 2000cp/2500cp	Fast/economy 83 ft ² /hour	Normal/productivity 42 ft ² /hour	Best/photo 17 ft²/hour			
3000cp/3500cp	92 ft ² /hour	46 ft ² /hour	18 ft²/hour			
3800cp (2800cp) Native	92 (83) ft²/hour	29 (28) ft ² /hour ⁺	18 (17) ft²/hour			
High speed		49 (47) ft²/hour ⁺	32 (29) ft²/hour			
aximum resolution	600 dpi					
minimum line width	0.003 in.					
line accuracy	±0.2% of specified page	0				
nedia handling	Sheet feed, roll feed, aut	omatic cutter, take-up reel (t	take-up reel is optional on 200	Ocp Series)		
nedia sizes	Sheet	Roll				
2000ср/2500ср/2800ср	width: 8.3 in. to 36 in.	width: 24 in., 36 in.				
3000 cm/3500 cm/3800 cm	length: up to 63 in. width: 8.3 in to 54 in.	length: up to 150 ft. width: 24 in., 36 in., 42	in 51 in			
3000ср/3500ср/3800ср	length: up to 63 in.	length: up to 150 ft.	m., 54 m.			
nemory	Standard	Maximum				
2000cp/3000cp	8 MB/12 MB	68 MB				
2500ср/3500ср	36 MB, 4.3 MB HD	68 MB, 4.3 GB HD				
2800ср/3800ср		68 MB; Fiery RIP 512 M	B			
onnectivity	2000cp/3000cp: HP-GL/2, HP RTL, CALS, CGM-ATA					
languages	2500cp/3500cp:Adobe [®] PoslScript [®] 3™, HP-GL/2, HP RTL, CALS, CGM-ATA					
		PostScript 3, (PS, EPS, PDI	⁼ and TIFF)			
drivers	2000cp/2500cp/3000cp/3500cp Microsoft [®] Windows [®] : 95, 98, NT 3.51, 4.0; Macintosh: 7.1 – 8.0 QuickDraw					
PostScript (2500cp/3500cp) Microsoft [®] Windows			intosn: 7.1 – 8.0 QuickDraw			
AutoCAD [®]	3.1, 95, 98, 2000, NT 3.51, 4.0 Releases 10, 11 (DOS); 12 (Windows 3.1, 95, DOS); 13 (Windows 3.1, 95, NT 3.51, 4.0, DOS), 14 (Windows 95, 98, NT 4.0					
UNIX®		accepted via ZEHRaster P				
	2800cp/3800cp systems	supported: Microsoft Wine	dows: 95, 98, NT 4.0, UNIX $^{(\! \mathbb{R})}$,			
interfaces	2000cp/3000cp: Centro	onics parallel port, IEEE 12	84 compliant, optional HP Jetdi	rect network interface card		
	2500cp/3500cp: Centronics parallel port, IEEE 1284 compliant, Ethernet/EtherTalk					
and a set of the set o		nics parallel port, IEEE 128	34 compliant, Ethernet, USB			
automatic interface switching	Yes			6		
iery X2 RIP software				/ise 2.0 technology (PANTONE® color matching,		
2800cp/3800cp) automatic interface switching				e profiles), including ColorWise Pro Tools ports with auto-switching support for EtherTalk,		
dolonialic interface switching	TCP/IP and Novell IPX pr			sons with dolo-switching support for Entertaik,		
varranty		ree, on-site, next-business-c	av service			
hysical characteristics						
inysical endracteristics	2000cp Series	3000cp Seri	es RIP			
vidth x depth x height/weight	61 in. x 29 in. x 48 in./			x 11 in. x 14 in./11.5 lbs.		
nvironmental specifications						
emperature ranges		Storage: –40°F to 158°F; F	RIP storage: -4°F to 140°F			
perating humidity	20% to 80% RH					
	Requirements: 100 to 24	0 V AC ±10% 2 A max; 50) to 60 Hz			
oower						
	Consumption: 153 watts					
	Consumption: 153 watts Sound pressure level—20	00cp Series: Printing: 42 d	B (A), Idle: <26 dB (A); 3000cp) Series: Printing: 46 dB (A), Idle: <30 dB (A)		
coustic emissions•	Consumption: 153 watts Sound pressure level—20	00cp Series: Printing: 42 d	B (A), Idle: <26 dB (A); 3000cp Is (A), Idle: <3.9 Bels (A); 3000c	Series: Printing: 46 dB (A), Idle: <30 dB (A) cp Series: Printing: 6.0 Bels (A), Idle: <4.3 Bels (A)		
coustic emissions• egulatory compliance	Consumption: 153 watts Sound pressure level—20 Sound power level—2000	00cp Series: Printing: 42 d Dcp Series: Printing: 5.6 Be	ls (A), Idle: <3.9 Bels (A); 3000	cp Series: Printing: 6.0 Bels (A), Idle: <4.3 Bels (A)		
coustic emissions• egulatory compliance	Consumption: 153 watts Sound pressure level—20 Sound power level—2000 EU LVD, IEC 950 & EN 6	00cp Series: Printing: 42 d Dcp Series: Printing: 5.6 Be 0950 compliant; printer is	ls (A), Idle: <3.9 Bels (A); 3000	Series: Printing: 46 dB (A), Idle: <30 dB (A) cp Series: Printing: 6.0 Bels (A), Idle: <4.3 Bels (A) certified (GS mark). Printer is UL listed, CSA		
acoustic emissions• egulatory compliance nformation and safety	Consumption: 153 watts Sound pressure level—200 Sound power level—2000 EU LVD, IEC 950 & EN 6 certified, RIP is CSA NRT	00cp Series: Printing: 42 d Ocp Series: Printing: 5.6 Be 0950 compliant; printer is L/C certified	ls (A), Idle: <3.9 Bels (A); 3000 NEMKO approved; RIP is TUV	cp Series: Printing: 6.0 Bels (A), Idle: <4.3 Bels (A) certified (GS mark). Printer is UL listed, CSA		
power acoustic emissions• regulatory compliance nformation and safety electromagnetic compatibility	Consumption: 153 watts Sound pressure level—200 Sound power level—2000 EU IVD, IEC 950 & EN 6 certified, RIP is CSA NRT EU EMC directive compli	00cp Series: Printing: 42 d Ocp Series: Printing: 5.6 Be 0950 compliant; printer is L/C certified ant, FCC rules, Canada Dc	ls (A), Idle: <3.9 Bels (A); 3000 NEMKO approved; RIP is TUV	cp Series: Printing: 6.0 Bels (A), Idle: <4.3 Bels (A)		
acoustic emissions• regulatory compliance nformation and safety electromagnetic compatibility	Consumption: 153 watts Sound pressure level—200 Sound power level—2000 EU IVD, IEC 950 & EN 6 certified, RIP is CSA NRT EU EMC directive compli products (Class A when c	00cp Series: Printing: 42 dl 0cp Series: Printing: 5.6 Be 0950 compliant; printer is L/C certified ant, FCC rules, Canada Dc connected to LANs)	ls (A), Idle: <3.9 Bels (A); 3000 NEMKO approved; RIP is TUV	cp Series: Printing: 6.0 Bels (A), Idle: <4.3 Bels (A) certified (GS mark). Printer is UL listed, CSA		
acoustic emissions• egulatory compliance nformation and safety electromagnetic compatibility	Consumption: 153 watts Sound pressure level—200 Sound power level—2000 EU IVD, IEC 950 & EN 6 certified, RIP is CSA NRT EU EMC directive compli	00cp Series: Printing: 42 dl 0cp Series: Printing: 5.6 Be 0950 compliant; printer is L/C certified ant, FCC rules, Canada Dc connected to LANs)	ls (A), Idle: <3.9 Bels (A); 3000 NEMKO approved; RIP is TUV	cp Series: Printing: 6.0 Bels (A), Idle: <4.3 Bels (A certified (GS mark). Printer is UL listed, CSA		
acoustic emissions• egulatory compliance nformation and safety electromagnetic compatibility environmental compliance	Consumption: 153 watts Sound pressure level—200 Sound power level—2000 EU LVD, IEC 950 & EN 6 certified, RIP is CSA NRT EU EMC directive compli products (Class A when c US EPA ENERGY STAR® com	00cp Series: Printing: 42 d Ocp Series: Printing: 5.6 Be 0950 compliant; printer is L/C certified ant, FCC rules, Canada Dc connected to LANs) apliant	ls (A), Idle: <3.9 Bels (A); 3000 NEMKO approved; RIP is TUV oC. Australia ACA, New Zealar	cp Series: Printing: 6.0 Bels (A), Idle: <4.3 Bels (A) certified (GS mark). Printer is UL listed, CSA		
coustic emissions• egulatory compliance nformation and safety lectromagnetic compatibility nvironmental compliance ordering information 2000cp 25	Consumption: 153 watts Sound pressure level—200 Sound power level—2000 EU LVD, IEC 950 & EN 6 certified, RIP is CSA NRT EU EMC directive compli products (Class A when c US EPA ENERGY STAR® com	00cp Series: Printing: 42 d Ocp Series: Printing: 5.6 Be 0950 compliant; printer is L/C certified ant, FCC rules, Canada De connected to LANs) opliant 0cp 3800cp options	ls (A), Idle: <3.9 Bels (A); 3000 NEMKO approved; RIP is TUV DC. Australia ACA, New Zealar and accessories	cp Series: Printing: 6.0 Bels (A), Idle: <4.3 Bels (A) certified (GS mark). Printer is UL listed, CSA nd MoC and China requirements for Class B		
coustic emissions• egulatory compliance nformation and safety lectromagnetic compatibility nvironmental compliance ordering information 2000cp 25 pox contents C4703A C4	Consumption: 153 watts Sound pressure level—200 Sound power level—2000 EU LVD, IEC 950 & EN 6 certified, RIP is CSA NRT EU EMC directive compli products (Class A when c US EPA ENERGY STAR® com	00cp Series: Printing: 42 dl 0cp Series: Printing: 5.6 Bel 0950 compliant; printer is L/C certified ant, FCC rules, Canada Dc connected to LANs) upliant 0cp 3800cp 24A C6084A 16 MB n	ls (A), Idle: <3.9 Bels (A); 3000 NEMKO approved; RIP is TUV bC. Australia ACA, New Zealar and accessories nemory module C6231A	cp Series: Printing: 6.0 Bels (A), Idle: <4.3 Bels (A) certified (GS mark). Printer is UL listed, CSA and MoC and China requirements for Class B		
coustic emissions• egulatory compliance nformation and safety lectromagnetic compatibility nvironmental compliance ordering information 2000cp 25 pox contents C4703A C4 vrinter stand & media bin •	Consumption: 153 watts Sound pressure level—200 Sound power level—2000 EU LVD, IEC 950 & EN 6 certified, RIP is CSA NRT EU EMC directive compli products (Class A when c US EPA ENERGY STAR® com	00cp Series: Printing: 42 d Cop Series: Printing: 5.6 Be 0950 compliant; printer is L/C certified ant, FCC rules, Canada Do connected to LANs) apliant 0cp 3800cp options 24A C6084A 16 MB n 32 MB n	ls (A), Idle: <3.9 Bels (A); 3000 NEMKO approved; RIP is TUV pC. Australia ACA, New Zealar and accessories nemory module C6231A nemory module C6232A	cp Series: Printing: 6.0 Bels (A), Idle: <4.3 Bels (A) certified (GS mark). Printer is UL listed, CSA nd MoC and China requirements for Class B		
egulatory compliance nformation and safety lectromagnetic compatibility nvironmental compliance ordering information 2000cp 25 pox contents C4703A C4 printer stand & media bin ake-up reel	Consumption: 153 watts Sound pressure level—200 Sound power level—2000 EU LVD, IEC 950 & EN 6 certified, RIP is CSA NRT EU EMC directive compli products (Class A when c US EPA ENERGY STAR® com	00cp Series: Printing: 42 d 0cp Series: Printing: 5.6 Be 0950 compliant; printer is L/C certified ant, FCC rules, Canada Do connected to LANs) upliant 0cp 3800cp 24A C6084A • • • • • • • • • • • • • • • • • • •	Is (A), Idle: <3.9 Bels (A); 3000 NEMKO approved; RIP is TUV pC. Australia ACA, New Zealar and accessories nemory module C6231A nemory module C6232A spindle assembly C2376A	cp Series: Printing: 6.0 Bels (A), Idle: <4.3 Bels (A) certified (GS mark). Printer is UL listed, CSA nd MoC and China requirements for Class B		
ecoustic emissions• egulatory compliance nformation and safety electromagnetic compatibility environmental compliance ordering information 2000cp 25	Consumption: 153 watts Sound pressure level—200 Sound power level—2000 EU LVD, IEC 950 & EN 6 certified, RIP is CSA NRT EU EMC directive compli products (Class A when c US EPA ENERGY STAR® com	00cp Series: Printing: 42 d Dcp Series: Printing: 5.6 Be 0950 compliant; printer is L/C certified ant, FCC rules, Canada Dc connected to LANs) upliant 0cp 3800cp 24A C6084A 16 MB n 32 MB n 36-inch s 54-inch s	ls (A), Idle: <3.9 Bels (A); 3000 NEMKO approved; RIP is TUV pC. Australia ACA, New Zealar and accessories nemory module C6231A nemory module C6232A	cp Series: Printing: 6.0 Bels (A), Idle: <4.3 Bels (A) certified (GS mark). Printer is UL listed, CSA nd MoC and China requirements for Class B		
egulatory compliance nformation and safety electromagnetic compatibility environmental compliance protering information 2000cp 25 pox contents C4703A C4 pox contents C4703A C4 power cords e	Consumption: 153 watts Sound pressure level—200 Sound power level—2000 EU LVD, IEC 950 & EN 6 certified, RIP is CSA NRT EU EMC directive compli products (Class A when c US EPA ENERGY STAR® com	00cp Series: Printing: 42 dl 0cp Series: Printing: 5.6 Bel 0950 compliant; printer is L/C certified ant, FCC rules, Canada Dc connected to LANs) upliant 0cp 3800cp 24A C6084A 16 MB n 32 MB n 36-inch s 36-inch s	Is (A), Idle: <3.9 Bels (A); 3000 NEMKO approved; RIP is TUV bC. Australia ACA, New Zealar and accessories nemory module C6231A nemory module C6232A spindle assembly C2376A spindle assembly C6248A	certified (GS mark). Printer is UL listed, CSA and MoC and China requirements for Class B As an ENERCY STAR [®] Partner, Hewlet:Packard Company has determined with this protocy. Hewlet:Packard Company has determined in this protocy. Hewlet:Packard Company has determined in this protocy. Adobe [®] PastScript [®] 3 TM and PressReady are trademarks of Adobe [®] PastScript [®] 3 TM and PressReady are trademarks of Adobe [®] CostScript [®] 3 TM and PressReady are trademarks of Adobe [®] CostScript [®] 3 TM and PressReady are trademarks of Adobe [®] CostScript [®] 3 TM and PressReady are trademarks of Adobe [®] PastScript [®] 3 TM and PressReady are trademarks of Adobe [®] CostScript [®] 3 TM and PressReady are trademarks of Adobe [®] CostScript [®] 3 TM and PressReady are trademarks of Adobe [®] CostScript [®] 3 TM and		
egulatory compliance nformation and safety electromagnetic compatibility environmental compliance ordering information 2000cp 25 pox contents C4703A C4 orinter stand & media bin ake-up reel oll-feed spindle	Consumption: 153 watts Sound pressure level—200 Sound power level—2000 EU LVD, IEC 950 & EN 6 certified, RIP is CSA NRT EU EMC directive compli products (Class A when c US EPA ENERGY STAR® com	00cp Series: Printing: 42 dl 0cp Series: Printing: 5.6 Bel 0950 compliant; printer is L/C certified ant, FCC rules, Canada Dc connected to LANs) upliant 0cp 3800cp 24A C6084A 16 MB n 32 MB n 36-inch s 36-inch s	Is (A), Idle: <3.9 Bels (A); 3000 NEMKO approved; RIP is TUV bC. Australia ACA, New Zealar and accessories nemory module C6231A nemory module C6232A spindle assembly C6248A ake-up reel C6246A n storage container C6236A	certified (GS mark). Printer is UL listed, CSA and MoC and China requirements for Class B As an ENERCY STAR® Partner, Hewlett Packard Company has determined that this product meets ENERCY STAR® guidelines to energy efficiency. Adobe®, the Adobe logo, Adobe® PostScript® 3™ and PressRedy are trademarks of Adobe Systems Incorporated. Macintosh is a trademark of Apple Computer, Inc. registered it the U.S.A. and other countries. Microsoft®, Windows and Windows NT are either registered trademarks or trademarks		
egulatory compliance nformation and safety lectromagnetic compatibility nvironmental compliance ordering information 2000cp 25 prodering information 2000cp 25	Consumption: 153 watts Sound pressure level—200 Sound power level—2000 EU LVD, IEC 950 & EN 6 certified, RIP is CSA NRT EU EMC directive compli products (Class A when c US EPA ENERGY STAR® com	00cp Series: Printing: 42 dl 0cp Series: Printing: 5.6 Bel 0950 compliant; printer is L/C certified ant, FCC rules, Canada Dc connected to LANs) upliant Ocp 3800cp 24A C6084A •	Is (A), Idle: <3.9 Bels (A); 3000 NEMKO approved; RIP is TUV bC. Australia ACA, New Zealar and accessories nemory module C6231A nemory module C6232A spindle assembly C6248A ake-up reel C6246A n storage container C6236A	certified (GS mark). Printer is UL listed, CSA and MoC and China requirements for Class B As an ENERGY STAR [®] Partner, Hewlett-Packard Company has determined that this product meets ENERGY STAR [®] guidelines for energy efficiency. Adobe [®] , the Adobe logo, Adobe [®] PostScript [®] 3 TM and PressReady are trademarks of Adobe Systems Incorporated. Mocintosh is a trademarks of Adobe Systems Incorporated. Mocintosh is a trademarks of Adobe Systems Incorporated. Mocintosh is a trademark of Apple Computer, Inc. registered in the U.S.A. and other countries. Microsoft [®] , Windows and Windows NT are either registered trademarks or trademarks of Microsoft Corp. in the United States and other countries.		
egulatory compliance nformation and safety lectromagnetic compatibility nvironmental compliance ordering information 2000cp 25 pox contents C4703A C4 printer stand & media bin ake-up reel oll-feed spindle • up designjet cp ink system dye • up porinting material sample • sser documentation • utter knife & holder •	Consumption: 153 watts Sound pressure level—200 Sound power level—2000 EU LVD, IEC 950 & EN 6 certified, RIP is CSA NRT EU EMC directive compli products (Class A when c US EPA ENERGY STAR® com	00cp Series: Printing: 42 dl 0cp Series: Printing: 5.6 Bel 0950 compliant; printer is L/C certified ant, FCC rules, Canada Dc connected to LANs) upliant Ocp 3800cp 24A C6084A • <	Is (A), Idle: <3.9 Bels (A); 3000 NEMKO approved; RIP is TUV bC. Australia ACA, New Zealar and accessories nemory module C6231A nemory module C6232A spindle assembly C6248A ake-up reel C6246A n storage container C6236A	certified (GS mark). Printer is UL listed, CSA and MoC and China requirements for Class B Mode Testory 3 Mode		
egulatory compliance information and safety lectromagnetic compatibility nvironmental compliance ordering information 2000cp 25 pox contents C4703A C4 printer stand & media bin ake-up reel oll-feed spindle • pup designiet cp ink system dye • up printing material sample • ser documentation • utter knife & holder • etdirect network card	Consumption: 153 watts Sound pressure level—200 Sound power level—2000 EU LVD, IEC 950 & EN 6 certified, RIP is CSA NRT EU EMC directive compli products (Class A when c US EPA ENERGY STAR® com	00cp Series: Printing: 42 d 0cp Series: Printing: 5.6 Be 0950 compliant; printer is L/C certified ant, FCC rules, Canada Dc connected to LANs) upliant 0cp 3800cp 24A C6084A 0 Gptions 16 MB n 36-inch s 54-inch s 36-inch t Ink syster Cleaning	Is (A), Idle: <3.9 Bels (A); 3000 NEMKO approved; RIP is TUV bC. Australia ACA, New Zealar and accessories nemory module C6231A nemory module C6232A spindle assembly C6248A ake-up reel C6246A n storage container C6236A	certified (GS mark). Printer is UL listed, CSA and MoC and China requirements for Class B MoC and China requirements for Class B As an ENERGY STAR [®] Partner, Hewlett-Packard Company has determined that this product meets ENERGY STAR [®] guidelines for energy efficiency. Adobe [®] , the Adobe logo, Adobe [®] PostScript [®] 3 TM and PressReady are trademarks of Adobe Systems Incorporated. Macintosh is a trademark of Apple Computer, Inc. registered the ULSA. and other countries. Microsoft [®] , Windows and Windows NT are either registered trademarks or trademarks of Microsoft Corp. in the United States and other countries. Microsoft [®] , windows and a registered trademark of the Open Group in the United State and other countries. PANITONE [®] is a registered trademark of Pantone, Inc. Energy Star is a registered trademark of the Open Group in the United State and other countries. PANITONE [®] is a registered trademark of Pantone, Inc. Energy Star is a registered trademark of the Open Group in the United State and other countries. PANITONE [®] is a registered trademark of Pantone, Inc. Energy Star is a registered trademark of the Open Group in the United State		
egulatory compliance nformation and safety electromagnetic compatibility environmental compliance prdering information 2000cp 25 poox contents C4703A C4 poox contents C4703A C4 pointer stand & media bin ake-up reel oll-feed spindle power cords ap designjet cp ink system dye	Consumption: 153 watts Sound pressure level—200 Sound power level—2000 EU LVD, IEC 950 & EN 6 certified, RIP is CSA NRT EU EMC directive compli products (Class A when c US EPA ENERGY STAR® com	00cp Series: Printing: 42 dl 0cp Series: Printing: 5.6 Bel 0950 compliant; printer is L/C certified ant, FCC rules, Canada Dc connected to LANs) upliant Ocp 3800cp 24A C6084A • <	Is (A), Idle: <3.9 Bels (A); 3000 NEMKO approved; RIP is TUV bC. Australia ACA, New Zealar and accessories nemory module C6231A nemory module C6232A spindle assembly C6248A ake-up reel C6246A n storage container C6236A	certified (GS mark). Printer is UL listed, CSA and MoC and China requirements for Class B Mode Testory 3 Mode		

*Approximate speeds on HP Coated Paper. [†]HP Heavyweight Coated Paper. [■]best/photo modes and high speed modes. • Per ISO DP7779. Typical emissions at 1 meter by-stander position for pressure

The information in this document is subject to change without notice.

www.hp.com/go/designjet © Hewlett-Packard Company Printed in the United States 8/00 5980-2211EUS